# 1756-OF8/A1756OF8

Model	1756-OF8
Brand	Original
Category	<u>Module</u>
Product Series	ControlLogix
Output Channels	8 isolated channels
Output Signals	Configurable per channel for voltage or current
Output Ranges	Voltage: -10V to +10V, 0 to 10V, 0 to 5V; Current: 0 to 20 mA or 4 to 20 mA
Decelution	
Resolution	16-bit
Calibration Accuracy	0.05%
Calibration Accuracy	0.05%
Calibration Accuracy Backplane Current	0.05% 5.1 VDC @ 200 mA; 24 VDC @ 275 mA
Calibration Accuracy  Backplane Current  Update Rate / Settling Time	0.05%  5.1 VDC @ 200 mA; 24 VDC @ 275 mA  1 ms (module startup)
Calibration Accuracy  Backplane Current  Update Rate / Settling Time  Isolation Voltage	0.05%  5.1 VDC @ 200 mA; 24 VDC @ 275 mA  1 ms (module startup)  250V (channel-to-channel and channel-to-backplane)

### Note:

Invshop recommends that you inquire with the original factory or its agents about the latest production status and technical information about 1756-OF8. The product parameters displayed on Invshop are entered by Invshop engineers according to the specifications, and efforts have been made to minimize errors, but we cannot guarantee the complete correctness of the parameters. Please refer to the specification sheet!

## https://www.invshop.com



## https://www.invshop.com



## https://www.invshop.com

