

# CK3XAB4M000W4400 Intermec CK3 Rugged Mobile LCD Screen Quality Product

|                                |                                              |
|--------------------------------|----------------------------------------------|
| Model                          | CK3XAB4M000W4400                             |
| Brand                          | Intermec                                     |
| Category                       | <a href="#">Other Industrial LCD display</a> |
| Product Series                 | ABB ESB Series                               |
| Rated Operational Current (Ie) | 40 A at 400V AC                              |
| Number of Poles                | 4                                            |
| Rated Insulation Voltage (Ui)  | 690 V AC                                     |
| Rated Operational Voltage (Ue) | 400 V AC                                     |
| Motor Power at 400V AC         | 18.5 kW                                      |
| Utilization Category           | AC-3 (Squirrel-cage motors)                  |
| Coil Control Voltage           | 230 V AC, 50/60 Hz                           |
| Terminal Type                  | Screw Clamp                                  |
| Standards Compliance           | IEC/EN 60947-4-1, UL 508                     |

## Note:

Invshop recommends that you inquire with the original factory or its agents about the latest production status and technical information about CK3XAB4M000W4400. The product parameters displayed on Invshop are entered by Invshop engineers according to the specifications, and efforts have been made to minimize errors, but we cannot guarantee the complete correctness of the parameters. Please refer to the specification sheet!

<https://www.invshop.com>



<https://www.invshop.com>